



# IP CAMERA HS-T058SM-G

- H.265 / H.264 / MJPEG
- 4MP ( 2560 × 1440 )
- 30 ~ 50 M IR night view distance
- 3D DNR, True WDR, HLC, BLC
- ICR auto switch, true day / night
- Built-in micro SD card slot, up to 256GB
- Support ROI coding
- Support three streams
- IP67 ingress protection
- Intelligent analytics: Exception, Line Crossing, Intrusion

**RoHS** CE FC





## HS-T058SM-G

Camera			
Image Sensor	1 / 3" CMOS		
Image Resolution	2560 × 1440		
Electronic Shutter	1/ 2 s ~ 1 / 100,000 s		
Min. Illumination	0.005 lux @ F1.6, AGC ON; 0 lux with IR		
Lens	EVF 2.8 ~ 12 mm @F1.4		
FOV	Horizontal	Vertical	Diagonal
	92° ~31°	48° ~17.2°	112° ~35.6°
Lens Mount	Ø14		
IR Distance	30~50 m		
WDR	WDR (120db)		
Day & Night	ICR auto switch		
BLC	YES		
HLC	YES		
Digital Defog	-		
Digital DNR	3D DNR		
Angle Adjustment	Pan: 0° ~360° ; Tilt:0° ~90° ;Rotation: 0° ~360°		

Image	
Video Compression	Main Strerm: H.265 / H.264 Sub/Third Strerm: H.265 / H.264 / MJPEG
H.265 Compression Standard	Main Profile @Leve4.1 High Tier
Resolution	4MP ( 2560 × 1440 ), 3MP ( 2304 × 1296 ), 1080P ( 1920 1080 ),720P ( 1280 × 720 ), D1, CIF, 480 × 240
Main Stream (S1)	60Hz : 4MP/3MP/1080P @30fps 50Hz : 4MP/3MP/1080P @25fps
Sub Stream (S2)	60Hz : 720P / D1 / CIF @30fps 50Hz : 720P / D1 / CIF @25fps
Third Stream (S3)	60Hz : D1 / 480x240 /CIF @30fps 50Hz : D1 / 480x240 /CIF @25fps
Bit Rate	64 Kbps ~ 8 Mbps
Bit Rate Type	VBR / CBR
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately

Audio	
Audio Compression	-
Two-way audio	-

Interfaces	
Network	RJ45
Video Output	-
Audio line in	1CH External MIC
Audio line out	-
Alarm Input	-
Alarm Output	-

Storage	
SD card	Built-in micro SD card slot; up to 256GB
Network remote storage	YES
Hardware Reset	YES

DORI Distance				
Lens	Detect	Observe	Recognize	Identify
2.8~12mm(W)	63.99m (209.94ft)	25.60m (83.98ft)	12.80m (41.99ft)	6.40m (20.99ft)
2.8~12mm(T)	188.65m (618.93ft)	75.46m (247.57ft)	37.73m (123.78ft)	18.86m (61.87ft)

Functions	
Remote Monitoring	Web browsing, CMS remote control
Online Connection	Support simultaneous monitoring for up to 3 users Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, PPPoE, DDNS, SMTP, FTP, 802.1x, SNMP, UPnP, HTTP, HTTPS, QoS
Interface Protocol	ONVIF
Smart Alarm	Motion detection; SD card full; SD card error
Intelligent Analytics	Exception, Line Crossing, Intrusion
General function	Watermark, IP address filtering, video mask, heartbeat, illegal login lock, corridor pattern
PoE	YES

Others	
Power Supply	DC12V / PoE
Power Consumption	< 8W
Operating Environment	- 30 ° C ~ 60 ° C (-22° F~140° F) Humidity: less than 95 % (non-condensing)
Dimensions	80.3 × 80.5 × 217.8 mm
Weight	Approx. 650g
Installation	Ceiling mounting ; Wall mounting
Ingress Protection	IP67
HVER	B

Accessories		
B627	B640	B639
B615	B616	B628