

Standard PoE Switch HS-PSW162-B

Product Features

- Total 300W power supply
- 16 ports POE
- 2 ports Uplink (1 co-share port with SFP)
- 1 port SFP
- Support surge protection for both power and RJ45 ports
- Power supply supports overloaded and over temperature protection
- Separate PoE and DC circuit, reduce interference

Specifications

Model	HS-PSW162-B	
Ethernet Port	PoE	RJ-45 x 14, 10/100/1000Mbps RJ-45 x 2, 10/100/1000Mbps
	Uplink	RJ-45 x 2, 10/100/1000Mbps
	SFP	1, 10/100/1000Mbps
PoE Consumption	Port 1 ~ 14 ≤ 30W	
	Port 15 ~ 16 ≤ 60W	
	Total Consumption ≤ 300W	
PoE Power Management	YES (Auto)	
PoE Pin Define	PoE 1~14 port : 12 (+), 36 (GND) PoE 15~16 port : 1245 (+), 3678 (GND)	
PoE Standard	IEEE 802.3i , IEEE 802.3u , IEEE802.3ab , IEEE802.3x , IEEE802.3at/af/bt	
Backplane Bandwidth	12.8 Gbps	
PoE Watchdog	port 1~16	
Packet Buffer Memory	-	
MAC Table Size	8K	
Flow Control	YES (Auto)	
Transmission Distance	10/100Mbps / MAX 250m 1000Mbps / MAX 100m	
Power Supply	AC 110V ~ 220V	
Operating Temperature	-30°C ~ 60°C (-22° F~140° F)	
Operating Humidity	10% ~ 90%	
Lightning Protection	General Mode 6KV	
ESD Protection	8KV	
Weight	2.84kg	
Dimension(W × D × H)	430 x 180 x 45 mm	



Dimension (mm)

