

# Standard PoE Switch HS-PSW244-B

## Product Features

- Total 300W power supply
- 24 ports POE
- 2 ports Uplink
- Support surge protection for both power and RJ45 ports
- Power supply supports overloaded and over temperature protection
- Separate PoE and DC circuit, reduce interference

## Specifications

Model	HS-PSW244-B	
Ethernet Port	PoE	RJ-45 x 22, 10/100Mbps RJ-45 x 2, 10/100/1000Mbps
	Uplink	RJ-45 x 2, 10/100Mbps
PoE Consumption	Port 1 ~ 22 ≤ 30W	
	Port 23 ~ 24 ≤ 60W	
	Total Consumption ≤ 300W	
PoE Power Management	YES (Auto)	
PoE Pin Define	PoE 1~22 port : 12 (+), 36 (GND) PoE 23~24 port : 1245 (+), 3678 (GND)	
PoE Standard	IEEE 802.3i , IEEE 802.3u , IEEE802.3ab , IEEE802.3x , IEEE802.3at/af/bt	
Backplane Bandwidth	12.4 Gbps	
PoE Watchdog	port 1~24	
Packet Buffer Memory	-	
MAC Table Size	8K	
Flow Control	YES ( Auto )	
Transmission Distance	10Mbps / 250M 100Mbps / 130M	
Power Supply	AC 110V ~ 220V	
Operating Temperature	-30° C ~ 60° C ( -22° F~140° F)	
Operating Humidity	10% ~ 90%	
Lightning Protection	General Mode 6KV	
ESD Protection	8KV	
Weight	2.84kg	
Dimension( W × D × H )	430 x 180 x 45 mm	



## Dimension (mm)

