



Wi-Fi IP CAMERA HS-T101KV-W

- H.265 / H.264
- 4MP (2560 x 1440)
- 20 m IR night view distance
- 3D DNR, Digital WDR
- Support two-way audio
- Built-in micro SD card slot, up to 256 GB
- ICR auto switch, true day / night
- Support ROI coding
- IP65 ingress protection

RoHS CE FC



Camera	
Image Sensor	1 / 3 " CMOS
Image Size	2560 x 1440
Electronic Shutter	1 / 25 s ~ 1 / 10000 s
Min. Illumination	0.01 lux (color & B/W) ; 0 lux with IR on
Lens	Board 2.8 mm @F/2.0
Horizontal view Angle	106°
IR Distance	20 M
Day & Night	Auto switch (by software)
WDR	YES
BLC	YES
HLC	YES
Digital Defog	-
Digital DNR	3D DNR
Image	
Video Compression	H.265 / H.264
H.265 Compression Standard	MP, Level 5.0
Main Stream (S1)	2560 x 1440, 2304 x 1296, 1920 x 1080, 1280 x 720 @30fps
Sub Stream (S2)	1280 x 720, 704 x 480, 352 x 240 @30fps
Third Stream (S3)	352 x 240 @30fps
Bit Rate	64 Kbps ~ 7 Mbps
Bit Rate Type	VBR / CBR
Image Settings	Brightness / Sharpness / Contrast / Hue / Saturation / Denoise Sensitivity / WDR / White Balance / Flicker-less / Shutter Speed / Mirror / Flip / ICR Control / Privacy Mask / Backlight Compensation
ROI	YES
Audio	
Audio Compression	G.711U
Two-way audio	YES
Interfaces	
Network	RJ45
Audio in	1 CH, Built-in MIC
Audio out	1 CH, Built-in Speaker 1W
Alarm Input	-
Alarm Output	-



HS-T101KV-W

Wi-Fi	
Wireless Standards	IEEE 802.11b/g/n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	20MHz
Security	WEP / WPA-PSK / WPA2-PSK
Storage	
Video Format	AVI
SD card	Built-in micro SD card slot; up to 256GB
Network remote storage	YES
Functions	
Remote Monitoring	Edge / Chrome / Firefox
Online Connection	Live View for up to 5 clients
Network Protocol	DHCP, DNS, FTP, HTTP, ICMP, IPv4, NTP, RTP, RTCP, RTSP, SMTP, TCP/IP, UDP, UPnP, ARP, Multicast, HTTPS, QoS
Interface Protocol	ONVIF
Intelligent/Smart	Motion Detection, Audio Alarm, SD Card Error, SD Card Full, IP Address Conflict, Network Disconnection
General function	System Information, Storage Setting, Video/Audio Setting, Intelligent Setting, Alarm Setting, Network Setting, Security Setting, Maintenance
PoE	-
Others	
Power Supply	DC 12V
Power Consumption	< 7W
Operating Environment	- 10 °C ~ 50 °C (14° F ~ 122° F) Humidity: <85 % (non-condensing)
Dimensions	148.8 x 64 x 87.6 mm
Weight	Approx. 320g
Ingress Protection	IP65